

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

TANGAZO LA SERIKALI NA. 171 la tarehe 21/3/2025

**SHERIA YA KODI YA ONGEZECO LA THAMANI,
(SURA YA 148)**

AMRI

(Imetengenezwa chini ya kifungu cha 6)

AMRI YA MSAMAHA WA KODI YA ONGEZECO LA THAMANI KATIKA MRADI WA
UENDELEZAJI NA UENDESHAJI WA KONGANI YA VIWANDA KWA KAMPUNI YA
SINO TAN KIBAHA INDUSTRIAL PARK YA MWAKA 2025

Jina

1. Amri hii itajulikana kama Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa Uendelezaji na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan Kibaha Industrial Park ya mwaka 2025 na itachukuliwa kuwa imeanza kutumika tarehe 26 Agosti, 2024.

Msamaha

2. Kwa kuzingatia masharti yaliyoainishwa katika aya ya 3, na masharti mengine yoyote yanayoweza kuainishwa na Kamishna Mkuu wa Mamlaka ya Mapato Tanzania, kodi ya ongezeko la thamani kwa bidhaa na huduma zilizoainishwa katika Jedwali la Amri hii, zilizoingizwa ndani ya nchi au kununuliwa kabla ya kibali kupitia forodha na au kwa niaba ya Kampuni ya Sino Tan Kibaha Industrial Park kwa ajili ya mradi wa uendelezaji na uendeshaji wa kongani ya viwanda inasamehewa.

Masharti

3. Msamaha uliotolewa chini ya Amri hii utakoma na Kodi ya Ongezeko la Thamani itapaswa kulipwa kana kwamba Amri hii haijatolewa ikiwa bidhaa au huduma zitatumika kwa matumizi mengine au kuhamishwa au kuuzwa kwa mtu mwingine ambaye hastahili kupata manufaa yanayotolewa na Amri hii.

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

Ukomo

4. Amri hii itafika ukomo tarehe 26 Agosti, 2028 na inaweza kuongezewa muda kwa kuzingatia masharti ya mkataba wa utekelezaji baina ya Kampuni ya Sino Tan Kibaha Industrial Park na Kituo cha Uwekezaji Tanzania kwa niaba ya Serikali ya Jamhuri ya Muungano wa Tanzania wa tarehe 23 Juni, 2023.

JEDWALI

(Limetengenezwa chini ya aya ya 2)

BIDHAA NA HUDUMA

No	Description	Unit of Measure	Quantity
A	DEVELOPER BUILDING MATERIAL ITEMS		
A1	MAIN BUILDING & CIVIL WORK; BUILDING MATERIAL		
1.	Marine Ply board	Sqm	102,2
2.	Prefabricated steel structure/bulding; Industrial Shade	Ton	41,91
3.	Coping; 270 x 75mm	NMB	10,58
4.	Copings; 300 x 75mm	NMB	249
5.	Copings; 400 x 400 x 100mm	NMB	96
6.	Culvert	NMB	400
7.	450x230x150mm blocks	NMB	1,281,
8.	450mm wide x 100mm thick wood composite	NMB	1,844
9.	35 x 85mm Aluminium louvred shells/screens/shading	NMB	468
10.	Paving Blocks; 200x100x80	SQM	21,98
11.	Paving Blocks; 600x600x50	SQM	48
12.	Kerbstone; 450x400x150mm	NMB	37,72
13.	Structural glass;10mm blue tinted complete with all accessories		
14.	steelworks; Prefabricated steel structure/ industrial shades; M/S Angle cleats;150x150mm	M	24,00
15.	Two lever mortice lock sets	NMB	
16.	Butt hinges; 100mm; aluminium	NMB	
17.	Ball bearing hinges; 127x 89x 3mm size	NMB	1,305

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

18.	Door stop; DS100 size 45x24mm	NMB	317
19.	Sprung door lever handle	NMB	230
20.	Lever mortice lock cylinder	NMB	306
21.	Medium duty with baccheck door closer	NMB	544
22.	Aluminium martin lever locksets	NMB	596
23.	Bathroom cylinder; 73mm case size	NMB	591
24.	Hinges; 75mm	NMB	2,366
25.	Pull handle; 150mm	NMB	2,148
26.	Cylinder spring latch lock	NMB	256
27.	Barrel bolts; 100 mm	NMB	256
28.	"D" handles; 100 mm	NMB	256
29.	Flush bolts	NMB	1,956
30.	6 mm thick; clear glass panel	NMB	169
31.	Fire doors (120min)	NMB	2
32.	Electronic doors	NMB	1
33.	Damp Proofing Membranes; 1000 Gauge	SQM	288,0
			61
34.	Damp Proofing Cause	M	29,96
			8
35.	20EC gammalin solution or the like	Litres	2,219,
			161
36.	Structural Adhesives; PVA; 955	NMB	150
37.	Bolts washer and nut: 10mm; Bolt-Washer-nut; 75mm Long; 16mm; Bolt-Washer-nut; 375mm Long; 20mm; Bolt-Washer-Nut; 120mm Long; Self drilling screws; 6x25mm; 6x50mm; 12mm; Bolt-Washer-Nut; 75mm Long; 25mm; Bolt-Washer-Nut; 300mm Long; Bolts; 10 mm dia x 50 mm long; two washers; two nuts; Bolts; 10 mm dia x 75 mm long; two washers; two nuts	NMB	74,08
			4
38.	Mild steel gutter and accessories: 110mm Gutter; Stopped ends; Running Outlets	NMB	1,290
39.	Natural Anodized aluminium: to Windows, to doors and walls	SQM	2,910
40.	Hardcore fill material;	CBM	178,3
			30
41.	Fill Material; G7	CBM	19,29
			2
42.	Subgrade; G15	CBM	45,56
			4
43.	Granular materials; G25	CBM	4,170
44.	Granular materials; G45	CBM	41,68
			0
45.	Sub-base; C1; with PI less than 6	CBM	23,46
			4
46.	750mm thick; median	CBM	3,596
47.	200mm thick; geen belts	CBM	10,80
			0

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

48.	Mild steel grills and metal work: 2100x1900;1500x1900;1500x800;800x800;900x2100;3000x2100;2600x2100;1400x2100;1350x2100;1500x1000;1500x900;2500x2550;1000x2550mm; 100mm diameter x 7000mm; primmed and gloss; steel flag posts; Sliding gates; 6000 x 2400mm; Sliding gates; 14000 x 2400mm; Pedestrian gate; 1200 x 2400mm; Barrel bolts; 12mm diameter; Tower bolts; 12mm dia x 500mm long	NMB	635
49.	Gypsym boards; 12mm thick; 10mm thick; Access panel	NMB	2,586
50.	Gypsym Cornince;	NMB	2,501
51.	Expansion joint material; 25mm thick; rubber flex fill material	SQM	2,709
52.	Roof structure in treated softwood: 50x50; 50x75mm;50x100mm; purlins, wallplate, bottomchord, truss members; 50x50mm brandering	M	37,78
53.	Hardwood: Frames, Architraves and grounding; Drawers, bearers	CBM	638
54.	Paint; Zinc Chromate	NMB	150
A2	SERVICE WORK; BUILDING MATERIAL		
A2.1	MECHANICAL SERVICES; PLUMBING & FIREFIGHTING		
1.	Pressure boosting set consisting of two identical vertical multistage stainless-steel pumps connected in parallel and mounted on a common base stainless steel pumps connected in parallel and mounted on a common base frame, with a control cabinet with integrated controller and provided with all the necessary fittings, Manufactured, Assembled and tested by the Manufacturer. The booster set will be fitted with an on/off switch for the supply voltage; 240Litres pressure vessel; Float switch; isolation valves; associated accessories	NMB	8
2.	European type WC; as to CASTLEWARE; or equal approved Close coupled floor standing with complete combination wash down outlet, dual flush cistern fittings 3.5litres or less for full flush, seat and cover and PVC Syphon fitting Oli. "P" or "S" trap pans; bedding outlets in mastic; fixing with brass screws to backgrounds requiring plugging.	NMB	1,197
3.	Asian type WC; as to CASTLEWARE; or equal approved Close coupled floor standing with complete combination wash down outlet, dual flush cistern fittings 3.5litres or less for full flush, seat and cover and PVC Syphon fitting Oli. "P" or "S" trap pans; bedding outlets in mastic; fixing with brass screws to backgrounds requiring plugging.	NMB	6

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

4.	Special Care Unit (Disable toilet); RAK, IDEAL STANDARD, ARROW or equal approved delivered complete in one box including WC, HWB, grab rails, hinged arm support, mixer tap, toilet roll holder etc	NMB	84
5.	White vitreous china Hand wash basin as to CASTLEWARE or equal approved; under counter type- 480mm diameter; complete with tap mixer capable to discharge water at a flow rate of 2litres/min. or less. Fixing with screws to backgrounds requiring plugging	NMB	898
6.	Single bowl Stainless steel wash kitchen sink; 1200 x 600mm; complete with Stainless-steel sink mixer with discharge flow rate of 4litres/min. complete with connecting accessories, fixing with screws to backgrounds requiring plugging	NMB	43
7.	White vitreous china Hand wash basin Wall hung Half pedestal 32430 size: 460x 580x210mm, Flexible, Magic 1 1/4x40 Bonomini or equal approved; complete with tap. Fixing with screws to backgrounds requiring plugging	NMB	158
8.	Urinal Bowl E905 Castleware or equal approved complete with top inlet press flushing valve per flush and associated accessories, fixing with brass screws to backgrounds plugging	NMB	61
9.	Shower rose, shower tray, shower mixer, Shower Rail with Square Head 30059 with fixing accessories.	NMB	42
10.	Shataff; ABS chrome with supreme Hose and wall holder as to CASTLE WARE or equal approved fixing with brass screws.	NMB	1,395
11.	Soap Dispenser AITANA AC70000Jc; fixing with brass screws to backgrounds plugging	NMB	540
12.	Mirrors; overall size 600 x 800mm high BELICE Bisel Mate, fixed to wall with CP screw and caps	NMB	960
13.	Toilet paper holder; chrome fixing with brass screws to backgrounds plugging	NMB	1,287
14.	Pillar Cock Basin Push Type Albeerto or approved equal, single lever basin mixer with popup Waste & 375mm long braided hoses and accessories or equal approved	NMB	1,136
15.	Angle valve to fortis brand with tringular handle and flange	NMB	4,165
16.	Heater of 10 liters of ARISTON or equal approved.	NMB	150

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

17.	Fire pump comprising electric duty pump, diesel engine driven standby pump and jockey for pressure sustainance. The automatic operation pumping set shall be in accordance with European Norm EN 12845 covering automatic fire systems, and UNI 10779 covering hydrant networks. The equipment shall be as Grundfos or approved equivalent and will be Hydro EN 32-160/177 YJS ADL-U3-A 50 Hz and comprise of: 1 No. Electric driven duty pump as NKF single-stage, end-suction, Automatic start/manual stop centrifugal pump set with a flow rate of 35m ³ /h against 8.8bars head and a power supply of 5.5Kw, 400V, 50Hz.;1 No. automatic diesel driven engine standby fire pump set with a flow 35m ³ /h against 8.8bars head and power 6.6kw	NMB	52
18.	Fire extinguisher bottles, by NAFFCO or equal approved of Dry powder (ABC), 6kg mounted on wall	NMB	368
19.	Fire extinguisher bottles, by NAFFCO or equal approved of Carbon dioxide (Co ₂), 5kg mounted on wall	NMB	440
20.	Fire Hose Reel as NAFFCO brand or equal approved, complete with standard cabinet for hose reel and two portable extinguishers, Hose diameter 25mm diameter, hose length 30m.	NMB	104
21.	Automatic Clean agent fire extinguisher model NHFC-6 MATIC gross weight 11kg (Extinguisher capacity 6kg), working pressure 15Bar, for Computer, Switchgears, server rooms and Sensitive data storage, coverage of 10m ² (Effective when mounted at height 3m from floor) for Vertical configurations, complete all necessities fittings. The units charged with Clean agent (HFC-236fa) and are fitted with a detection sprinkler head that is rated at 68°C. Capable of extinguisher fire type A, B, C and Electrical fires.	NMB	106
22.	Fire blanket of 6" X 6"	NMB	1
23.	Breeching Inlet Cabinet material mild steel, glass with wire meshed reinforcement, paint with Epoxy powder red as manufactured to BS 5041 complete with Breeching cabinet size: 595mm[W] x 395mm[H] x 295mm[D] & 4" x 2 Way	NMB	6
24.	Canvas flexible Fire Hose Reel, 30m long, 65mm diameter complete double compactment cabinet with supporting equipment	NMB	18
25.	2- way fire hydrant 2 x 63mm control valve with Female BS instantaneous outlet with inlet 100mm BS 10 flange complete with associate fittings	NMB	107
26.	100mm,50mm,40mm diameter HDPE pipes, black/blue color PN16 to ISO4427 and BS EN 12201 standards with PP Compression Fittings to BS EN 12001 for transferring water.	M	10,78

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

27.	100mm,50mm,40mm diameter non-return valves; HDPE fittings; 100mm,50mm 90 degree elbows & Tee; metering unit	NMB	516
28.	Hose reel, Dry/Wet Riserpipes and fittings in galvanized heavy grade material to BS 1387 and BS 1256: 150mm,100mm,50mm,25mm diameter Pipes	M	46,34
29.	Hose reel pipe fittings in galvanized heavy grade material to BS 1387 and BS 1256: 150mm,100mm,50mm,25mm diameter; Elbow;Tee;Union; Gate valve; High pressure landing valves-65mm; Flanged tee-100mm;reducers-100x75mm;Canva Flexible fire hose reel;30m Long; 65mm Diameter	NMB	3,246
A2.2	MECHANICAL SERVICES; HVAC & LIFTS		
1.	Refrigerant copper pipes complete with associated fittings, insulation; 6.4mm diam;9.5mm diam; 12.7mm diam; 15.9mm diam	M	10,17
2.	Armaflex (insulation)-1.8 per piece;6.4mm,9.5mm,12.7mm,15.9mm, AVS Srge protector, Mounted bracket	NMB	6,095
3.	Flexible cable of 3core x 2.5mm sqr control and power cables between units and DP switch	M	12,91
4.	Type of lift: Electric Passenger lift , Machine room less ;Drive system: (VVVF) with sleep mode option; Number of car: Two(2);Capacity of car:630kg -8 people; Stop designation; Number of stops/Openings: 4(G,1-2,Roof);Speed:1.0 m/s ;Openings: Center Openings (CO);Travelling distance:16m approximate; Shaft size (HW x HD):1726x1700mm; Lift pit:1300mm;Inside Car dimensions (CWxCD):1100x1400mm;Overhead Height:3650mm; Door opening: Two pannels, center opening ;Door net size 800mmx2100mm (WxH);Operation system: Duplex collective operation;Main power supply: 400Volts $\pm$ 5% of normal, 50Hz Three phase;Car lighting power supply: 220Volts, Single phase.	NMB	12
5.	Lift shaft lighting including cabling in mini-trunking and light fittings on the shaft wall, running from top of the shaft to the bottom, with intermediate fitting every approximately 3.3 meters for all lifts.	NMB	12
6.	Voltage stabilizer; Passanger Lift	NMB	12
A2.3	ELECTRICAL & ICT SERVICES		
1.	500kVA,33/0.4kV oil immersed transformer complete with drop out fuse including lightening arrestors, crossarms, pin insulators copper lugs for both sides HT and LT and all associated accessories as ABB or equal and approved	NMB	10

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

2.	315kVA,33/0.4kV oil immersed transformer complete with drop out fuse including lightening arrestors, crossarms, pin insulators copper lugs for both sides HT and LT and all associated accessories as ABB or equal and approved	NMB	46
3.	100kVA,33/0.4kV oil immersed transformer complete with drop out fuse including lightening arrestors, crossarms, pin insulators copper lugs for both sides HT and LT and all associated accessories as ABB or equal and approved	NMB	6
4.	Generator set of 3 Phase, 275kVA, 50Hz diesel generator sets with sound attenuated, auto start generator set and all features required for standby applications conveniently packaged together as Perkins/Caterpillar/olympian/Cummins or equal and approved	NMB	3
5.	Generator set of 3 Phase, 88kVA, 50Hz diesel generator sets with sound attenuated, auto start generator set and all features required for standby applications conveniently packaged together as Perkins/Caterpillar/olympian/Cummins or equal and approved	NMB	6
6.	400A TPN automatic changeover switch comprising of two 4-pole electrically and mechanically interlocked 400A motorised MCCB complete with controller AS PER ABB TYPE OR APPROVED EQUIVALENT.	NMB	3
7.	160A TPN automatic changeover switch comprising of two 4-pole electrically and mechanically interlocked 160A motorised MCCB complete with controller AS PER ABB TYPE OR APPROVED EQUIVALENT.	NMB	6
8.	12-Ways TPN free standing Main LV Panel Board with 400A TPN MCCB incomer, metal clad, cubical pattern to IP20 form 2b,with short circuit breaking capacity of 50KA at 415Vac,50HZ ,COMPRISING OF ABB switch gear and outgoing MCCBs of 63A TP (3 No),100A TP (9 No),comprising of 50kA Surge Arestor, Ammeter and voltmeter complete with 300kvar power factor correction as ABB type or equal and approved.	NMB	9
9.	12 Ways SPN distribution board DB-C with integral 63A/300mA MCCB incomer and final circuit MCBs of 10A SP (4No),20A SP(2No) and 32A SP(6No) as ABB TYPE or APROVED EQUIVALENT.	NMB	37
10.	12Ways TPN distribution board DB-GFA with integral 100A/300mA MCCB incomer and final circuit MCBs of 10A SP (4No),20A SP(24No) and 32A SP(5No) ,45A SP(3No)as ABB TYPE or APROVED EQUIVALENT.	NMB	13
11.	8 Ways TPN distribution board DB- FS with integral 100A/300mA MCCB incomer and final circuit MCBs of 10A SP (6 No),20A SP(12No) and	NMB	44

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

	32A SP(5No) ,45A SP(1No)as ABB TYPE or APROVED EQUIVALENT.		
12.	8 Ways TPN distribution board DB- GFB with integral 100A/300mA MCCB incomer and final circuit MCBs of 10A SP (4 No),20A SP(15No) and 32A SP(4No) ,45A SP(2No)as ABB TYPE or APROVED EQUIVALENT.	NMB	13
13.	8Ways SPN distribution board DB-F with integral45A 63A /300mA MCCB incomer and final circuit MCBs of 10A SP (2No),20A SP(3No) and 32A SP(3No) as ABB TYPE or APROVED EQUIVALENT.	NMB	40
14.	6Ways TPN distribution board DB-GH with integral 100A/300mA MCCB incomer and final circuit MCBs of 10A SP (5No),20A SP(3No), 32A SP(1No) and 45A TP(3NO) as ABB TYPE or APROVED EQUIVALENT.	NMB	7
15.	6 Ways SPN distribution board DB- A, D, E, F with integral 45A/300mA MCCB incomer and final circuit MCBs of 10A SP (2 No),20A SP(3No) and 32A SP(1No) as ABB TYPE or APROVED EQUIVALENT.	NMB	114
16.	4 Ways SPN distribution board DB-B with integral 32A/300mA MCCB incomer and final circuit MCBs of 10A SP (2 No),20A SP(1No) and 32A SP(1No) as ABB TYPE or APROVED EQUIVALENT.	NMB	38
17.	4-Ways TPN free standing Main LV Panel Board with 160A TPN MCCB incomer, metal clad, cubical pattern to IP20 form 2b,with short circuit breaking capacity of 50KA at 415Vac,50HZ ,COMPRISING OF ABB switch gear and outgoing MCCBs of 63A TP (1 No), 100A TP (3 No),comprising of 50kA Surge Arestor, Ammeter and voltmeter complete with 50kvar power factor correction as ABB type or equal and approved .	NMB	6
18.	Lighting type A:RECESSED LED PANEL RC-SL SQUARE 595-40W-6500 -WH-GP III WITH CODE NO.542004024510 AS OPPL TYPE OR APPROVED EQUIVALENT	NMB	555
19.	Lighting type B: LEDS DOWNLIGHT RC-HM R120-12W-3000K-WH-GP WITH SAP CODE 140048186 AS OPPL TYPE OR APPROVED EQUIVALENT	NMB	3,940
20.	Lighting type C:LEDS DOWNLIGHT RC-ESII R100-12W-600 WH NV WITH SAP CODE 140053271 AS OPPL TYPE OR APPROVED EQUIVALENT	NMB	1,332
21.	Lighting type D:LEDS CEILING LAMP,HC 300-10W-5700K RADAR PLUS -10 WITH SAP CODE 140056039 AS OPPL TYPE OR APPROVED EQUIVALENT.	NMB	873
22.	Lighting type E: LEDS -42-T8-1200MM 18-4000K	NMB	89

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

	GLASS-DBL -CT -COMPLETE WITH LED TUBE AS OPPLER TYPE OR APPROVED EQUIVALENT.		
23.	Lighting type F: LED BULKHEAD -E-13W-4000-FR-GP IP65 WITH CODE 543022000710.	NMB	1,843
24.	Lighting type G: LED BULKHEAD -E-9W-4000-FR-GP IP65 WITH CODE NO. 543022000710.	NMB	153
25.	CEILING FANS 50W, BLADE 56 INCH COMPLETE WITH HOOK, SWITCH AND REGULATOR AS PANASONIC MAKE OR APPROVED EQUIVALENT	NMB	1,619
26.	External light double arm 2x50W courtyard solar pole light, 6m high quality galvanised steel s-5days even cloudy days 8hours /day with 140AH battery, 70W solar panel complete with all required accessories like (light, battery, panel, charge control and pole) as OPPLER TYPE or approved equivalent	NMB	6
27.	Single arm light 70W Courtyard solar pole light, 12m high quality galvanised steel 3-5 days even cloudy days 8 hours/day with 140AH battery, 70W SOLAR panel Complete with concrete base and all required accessories like light, battery, panel charger control and pole) as opple type (brand) or approved equivalent.	NMB	542
28.	Electric cables; 4C x 25mm ² Cu,PVC/ PVC cable; 1C x 16mm ² Cu,PVC Green/Yellow earth cable; 1C x 10mm ² Cu,PVC Green/Yellow earth cable.; 4C x 240mm ² Cu, PVC/SWA/PVC cable from Main Supply passing through changeover switch to Sub -Main LV Panel Board.; 4C x 50mm ² Cu, PVC/SWA/PVC cable from Main Supply passing through changeover switch to Sub -Main LV Panel Board.; 1C x 120 mm ² PVC/Cu Green/Yellow earth cable.; 1C x 25mm ² PVC/Cu Green/Yellow earth cable.; 4C x 16mm ² Cu,PVC/ PVC cable from sub Panel Board to distribution board Lift.; 70sqmm 4core U/G cable.; 25sqmm 4core U/G cable; 1C x 16mm ² Cu,PVC Green/Yellow earth cable.; 1C x 6mm ² Cu, bare conductor for lightning protection; Earth wire cu 70mm ² ; 4C x 150mm ² Cu,PVC/ SWA/PVC cable from LV fuse to out door Low voltage panel.; 4C x 16mm ² Cu,PVC/SWA/ PVC cable from Main LV Panel Board to isolator; 1C x 16mm ² Cu,PVC Green/Yellow earth cable.;	M	76 137,2
29.	Cable tyer (8nr); 4C x 25mm ² Cu,PVC/ PVC cable; Cable lugs for 16mm ² cable; Cable glands for 4x25mm ² cable, 1C x 16mm ² Cu,PVC Green/Yellow earth cable., 3C x 10mm ² Cu,PVC/ PVC cable; Cable glands for 3x10mm ² cable , 1C x 10mm ² Cu,PVC Green/Yellow earth cable; Cable glands for 16mm ² cable (2nr)	NMB	2,608

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

30.	Copper Cables; 3C x 10mm ² Cu,PVC/ PVC cable; Single core 2.5 sqmm PVC copper cables from distribution Boards to all power outlet points; Single core 1.5 sqmm PVC copper cables from distribution Boards to all lighting outlet points ;	NMB	8	70,19
31.	PVC Heavy gauge Conduits, elbow and connectors for;100mm diam, 25mm diam, 20mm diam, 4way 20mm round box, Back box and cover; twin back box;	NMB	92	129,6
32.	Tangic; PVC Glue; 1Litre	NMB		324
33.	Trunking Installations;3-compartment PVC trunking 170 x 50mm to be recessed on walls(flush) and installed at skirting level complete with all necessary fixing accessories as MK	M	0	26,61
34.	Sockets, Switches, cooker control units, fan regulators, DP switches; 2 x13A raw power switched socket outlet complete with back box; 20A DP switch for water pump as Legrand or approved equivalent; TV, CAMERA, Data and Voice outlet points complete with back box; Cooker control unit 45A DP switched with neon lamp and integral 13A switch socket outlet flush as Legrand or approved equivalent; One way 1 gang light switch as Legrand or equivalent; One way 2 gang light switch as Legrand or equivalent; Two way 1 gang light switch as Legrand or equivalent; Intermediate light switch as Legrand or equivalent; Photocell unit c/w 16A TPN contactor for external lighting.;	NMB		7,256
35.	Isolators: 63A TP, Three phase Isolator for Lift; 32A TP, Three phase Isolator for Pump; 63A TP isolator; 120A TP isolator; Metering panel, 320A metering unit, 320A 4way TP outdoor low voltage panel; 120A TP Isolator	NMB		69
36.	Lighting arrestor; 33KV lightning arrestor C/w fuse Isolator; lightning protection including surge arrestors; Surge arrestors (11Sets)	NMB		58

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

37.	Lighting protection; Copper lugs-70sqmm-HT side; Copper lugs-25sqmm-HT side; Copper lugs-50sqmm-L/T side; 33KV Termination kit 50/25sqmm; Copper lugs-240sqmm-L/T side	NMB	96
38.	Termination Kit:33KV Termination kit 240/70sqmm; Metering unit (100A) for 100kVA transformer; Metering unit (160A) for 100kVA transformer; Metering unit (400A) for 315kVA transformer; Copper cable lugs 25/16sqmm; Copper cable lugs 50/25sqmm; Copper cable lugs 240/70sqmm; Raychem termination kit for the 3 core 33kV 185mmsq HT cable	NMB	814
39.	Electric Poles: 33kV HT Pole complete with all necessary conductors, insulators, supports and all installations accessories; Pin insulator complete with conic pin; Drop Out Fuse including Lightening Arrestors; 12m spun pre-stressed concrete pole (210)	NMB	510
40.	Galvanised Mild Steel Cable Trays; 450mm x 300mm GSM cable tray for power and data	M	13,340
41.	Capacitor Bank; Supply and install the 100kVAR power Factor Capacitor Bank switched in six steps,50,50kVAR; Solid copper air terminal as Furse complete with all mounting accessories	NMB	45
42.	25 x 3mm Bare copper tape, 70sqmm copper conductor, test clamp, earth rods, inspection pits complete with bonding to all RC column welding bars to be used as down conductor and all fixing accessories, disconnecting links, test links, discharge counter and others as per technical specification and drawings	M	996
43.	Fire Detection and Alarm system:2loops,4 zones conventional fire alarm control panel FP 2000 Series complete with power supply units, plug in modules, charger and 24 hours battery standby unit; conventional Photoelectric smoke detector with base; conventional Heat detector complete with base; Breakglass conventional call point; conventional sounder/bell; 33kV SF6 outdoor Load breaker switch	NMB	2,743
44.	Templates and accessories; Hot Dip Galvanized 33kv Angle Cross arm 7'4" x 4 x 2" x 8mm thick Long cross arm strut 33kV Pin insulator complete with spindle, bolt, washer and nut 33kV Disc insulators 33kV galvanised Jumper spindle complete with bolt, washer and nut Clevis adapter 6 bolt clamp J hook Bolt & Nuts x 12" x 3/8	NMB	5,140

*Amri ya Msamaha wa Kodi ya Ongezeko la Thamani Katika Mradi wa
Uendelezaji Na Uendeshaji wa Kongani ya Viwanda kwa Kampuni ya Sino Tan
Kibaha Industrial Park*

Tangazo la Serikali Na. 171 (linaendelea)

	3/4" nut 3/4" washer Danger plate Pole identifier Light duty universal section clamp (203 - 229) mm; Cable Lugs 33Kv 185mmsq HT		
45.	Barbed Wire; 2.5mm diam; 3mm soft binding wire	M	1,050
46.	Earthing Protection system: 2m earth rod complete with clamp; Red soil 5kg bags (33No); 20kg Salt bags (33No); Charcoal ash 5kg bag(33No)	NMB	132
47.	Stay: Stay rod(19);Stay bolt(19);Stay insulator(19);Stay block(19);Stay plate(19); Cross Arm 7'4"x4x2"	NMB	95
48.	Stay wire (228)	M	228
49.	Electrical; Fire detection& Alarm systems; Installation Accessories for system installation/commissioning; Earthing Electrical system to IEE	NMB	48

Dodoma,
11 Machi, 2025

MWIGULU LAMECK NCHEMBA MADELU
Waziri wa Fedha